



NOTE:  
TYPICAL INSTALLATION PLACES FERTILIZER ON CENTERLINE WITH CENTERLINE OF MOUNTING BOLTS OFF CENTER

**RH UNIT SHOWN  
LH IS MIRROR OPPOSITE**

**OPTIONAL TRASHWHEEL  
SHOWN**

**WEIGHT= 475LBS (NO ROW CLEANER)**

**MAX UPWARD LIFT ON FRAME= 500LBS**

TOLERANCES - ALL DIMENSIONS ARE IN INCH SYSTEM - UNLESS OTHERWISE NOTED:  
1-PLACE DECIMALS = ± .06 2-PLACE DECIMALS = ± .03 3-PLACE DECIMALS ± = .015

**DAWN** EQUIPMENT COMPANY  
BOX 497 SYCAMORE, ILLINOIS 60178 USA

REV	DATE	DESCRIPTION	BY

DRWN:	JDB	SCALE:	1/12
DATE:	8/4/11	APPROVED:	JDB
MATL:	BOM	FINISH:	PWDR COAT BLCK
NAME	6000 MOUNTING SPECS	DRAWING NUMBER	6000R (2011)
		REV	3

PLEASE NOTE:  
THIS DRAWING IS THE PROPERTY OF THE DAWN EQUIPMENT COMPANY AND IS NOT TO BE USED FOR ANY PURPOSE DETRIMENTAL TO ITS INTEREST. ALL DESIGN RIGHTS ARE RESERVED.